

1/1/2008

MATERIAL SAFETY DATA SHEET NPVLA 6-70

(Approved by U.S. Department of Labor "Essentially Similar" to Form LSB-00S-4)

Section I

MANUFACTURER'S NAME

CLEVELAND LITCHICHROME, INC.

STREET ADDRESS

1024 EAST WALL STREET

CITY, STATE AND ZIP CODE

FORT SCOTT, KANSAS 66701

EMERGENCY TELEPHONE NO.

(620) 223-3210 and (620) 223-0115 and (620) 223-6008

CHEMICAL NAME AND SYNONYMS

TRADE NAME

LITHICO CLEAR

CHEMICAL FAMILY

FORMULA

Section II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS

PIGMENTS	%	TLV (UNITS)	SOLVENTS	CAS	%
ACRYLIC RESINS		41 N/A	*Methyl Isobutyl Ketone	108-10-1	32
			*Xylol (Xylene)	1330-20-7	27
			*listed on SARA 313		
CATALYST			ADDITIVES		
VEHICLE			OTHERS		

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM CODE

Health 2 (Moderate) Flammability 3 (High) Reactivity 0 (Least)

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES

% TLV (UNITS)

Section III - PHYSICAL DATA

BOILING POINT (°F)	237° F	SPECIFIC GRAVITY (H2O=1)
VAPOR PRESSURE (MM Hg.)	(mm of Hs)@20°C: 11.9	PERCENT VOLATILE BY VOLUME (%)
VAPOR DENSITY (AIR=1)	(Air≈1) 3.7	EVAPORATION RATE (Ether=1)
SOLUBILITY IN WATER	Negligible	
APPEARANCE AND ODOR	Clear - Ketone	

Section IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED)	FLAMMABLE LIMITS	Vel	Vel
18°C/64°F (TCC) Lowest Flashing Component		1.3	7.5

EXTINGUISHING MEDIA

NFPA Class B Extinguishers (CO2 or Foam) - media: for class I B liquid fires

SPECIAL FIRE FIGHTING PROCEDURES

Water spray may be ineffective on fire but can protect fire fighters & cool closed containers

Use fog nozzles if water is used. Use air-supplied breathing masks.

UNUSUAL FIRE AND EXPLOSION HAZARDS

FLAMMABLE: Keep container tightly closed. Isolate from oxidizers, heat, sparks electric equipment and open flame.

Closed containers may explode if exposed to extreme heat. Applying to hot surfaces requires special precautions.

Date: 1-1-05

Section V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

Methyl Isobutyl Ketone 100ppm-	OSHA-PEL 100ppm	ACGIH-TLV 50ppm	ACGIH-STEL 75ppm
Xylol (Xylene) 100ppm-	OSHA-PEL 100ppm	ACGIH-TLV 100ppm	ACGIH-STEL 150ppm

EFFECTS OF EXPOSURE

INHALING: Anesthetic, Irritates respiratory tract. May cause serious nervous system depression.

SKIN OR EYE CONTACT: Primary irritation. **EFFECTS OF SWALLOWING AND CHRONIC OVER-EXPOSURE:**

Vapor harmful. Liquid causes eye irritation. Liquid may cause skin irritation. Harmful or fatal if swallowed.

EMERGENCY AND FIRST AID PROCEDURES

In case of contact with skin, flush with plenty of water. For eyes, flush with plenty of water for 15 minutes & get medical attention. If exposed to high concentration of vapor, remove to fresh air. If swallowed, CALL A PHYSICIAN IMMEDIATELY. DO NOT induce vomiting.

Section VI - REACTIVITY DATA

STABILITY	UNSTABLE	CONDITIONS TO AVOID
	STABLE X	Isolate from heat, sparks, electric equipment

INCOMPATIBILITY (Materials to avoid)

Isolate from strong oxidizers such as permanganate.

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon monoxide from burning

HAZARDOUS POMMERIZATION	MAY OCCUR	CONDITIONS TO AVOID
	WILL NOT OCCUR X	

Section VII - SPILL OR LEAK PROCEDURES**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Isolate from oxidizers, heat, sparks, electric equipment and open flame.

WASTE DISPOSAL METHOD

Recycle or incinerate observing local, state, and federal health, safety & pollution laws.

Section VIII - SPECIAL PROTECTION INFORMATION**RESPIRATORY PROTECTION**

The use of respiratory protection is advised when concentrations exceed the established exposure limits, (see section V). Depending on the airborne concentration, use a respirator or gas mask with appropriate organic vapor cartridge and cannister (NIOSH approved, if available) or supplied air equipment. A half mask may be used, however, a full face mask is recommended for high concentrations.

VENTILATION	LOCAL EXHAUST	SPECIAL
	Preferable	None
PROTECTIVE GLOVES	MECHANICAL (general)	OTHER
Recommended (must not dissolve in solvents)	Acceptable	None
	EYE PROTECTION	
	Eye goggles required.	

OTHER PROTECTIVE EQUIPMENT

None

Section IX - SPECIAL PRECAUTIONS**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Do not store above 49°C/120°F. Store large amounts in structures made for OSHA Class I B liquids. Avoid free fall of liquid

*Ground containers when pouring. Do not flame cut, saw braze or weld. Empty container hazardous! Continue all label precautions!

*Only applicable to 5 gallon containers or larger.

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY IS EXPRESSED OR

IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION. THE RESULTS TO FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS TO ITS USE.

This information and the product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of his use thereof. Date: 1-1-05

TLV (UNITS)

100

100

(Water=1): 0.836

100

8.3

DIATELY!

it & open flame.

sters
ended

d.

OR

BE OBTAINED
RELATED